



Test Report issued under the responsibility of:



TEST REPORT

IEC 62368-1

Audio/video, information and communication technology equipment

Part 1: Safety requirements

Report Number	E135494-A6011-CB-1
Date of issue.....	2019-06-28
Total number of pages	405

Applicant's name	TDK-LAMBDA UK LTD
Address	KINGSLEY AVE ILFRACOMBE EX34 8ES UNITED KINGDOM

Name of Test Laboratory preparing the Report	UL International Polska Sp. z o.o. Aleja Krakowska 81, 05-090 Sekocin Nowy, Poland
--	---

Test specification:	
Standard	IEC 62368-1:2014 (Second Edition)
Test procedure	CB Scheme
Non-standard test method.....	N/A

Test Report Form No	IEC62368_1B
Test Report Form(s) Originator	UL(US)
Master TRF.....	2014-03

Copyright © 2014 Worldwide System for Conformity Testing and Certification of Electrotechnical Equipment and Components (IECEE), Geneva, Switzerland. All rights reserved.


This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.



If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.

General disclaimer:

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory.
The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.

Test Item description :	Switch-mode Power Supply
Trade Mark	
Manufacturer	TDK-LAMBDA UK LTD KINGSLEY AVE ILFRACOMBE EX34 8ES UNITED KINGDOM
Model/Type reference	QM4 and QS4, QM5 and QS5, QM7 or QS7, QM8, QM8B and KQM5001V-x switch mode power supplies (followed by alphanumeric characters - see Model Differences section in Test Report for details of models and nomenclature)
Ratings	<p>QM4 or QS4 (550W): 100-240Vac nom, 47-440Hz, 9A rms max QM4 or QS4 (650W): 200-240Vac nom, 47-440Hz, 6A rms max QM4 or QS4 (550W): 144-318Vdc nom, 6Adc max QM4 or QS4 (650W): 239-318Vdc nom, 5Adc max</p> <p>QM5 or QS5 (700W): 100-240Vac nom, 47-440Hz, 11A rms max QM5 or QS5 (800W): 200-240Vac nom, 47-440Hz, 9A rms max QM5H or QS5H (700W): 100-240Vac nom, 47-440Hz, 11A rms max QM5H or QS5H (800W): 200-240Vac nom, 47-440Hz, 9A rms max QM5H or QS5H (1200W): 200-240Vac nom, 47-440Hz, 9A rms max</p> <p>QM5 or QS5 (700W): 144-318Vdc nom, 7Adc max QM5 or QS5 (800W): 239-318Vdc nom, 7Adc max QM5H or QS5H (700W): 144-318Vdc nom, 7Adc max QM5H or QS5H (800W): 239-318Vdc nom, 7Adc max QM5H or QS5H (1200W): 239-318Vdc nom, 7Adc max</p> <p>QM7 or QS7 (1200W): 100-240Vac nom, 47-440Hz, 19A rms max QM7 or QS7 (1500W): 166.7-240Vac nom, 47-440Hz, 14A rms max QM7 or QS7 (1200W): 144-318Vdc nom, 13Adc max QM7 or QS7 (1500W): 239-318Vdc, 9Adc max</p> <p>QM8 (1200W): 100-240Vac nom, 47-440Hz, 19A rms max QM8 (1500W): 166.7-240Vac nom, 47-440Hz, 14A rms max QM8 (1200W): 144-318Vdc nom, 13Adc max QM8 (1500W): 239-318Vdc, 10Adc max</p> <p>QM8B (1200W): 100-240Vac nom, 47-440Hz, 19A rms max QM8B (1500W): 166.7-240Vac nom, 47-440Hz, 14A rms max QM8B (2000W): 200-240Vac nom, 47-440Hz, 15A rms max QM8B (1200W): 144-318Vdc nom, 13Adc max QM8B (1500W): 239-318Vdc, 10Adc max</p>

		QM8B (2000W): 239-318Vdc, 12Adc max	
Testing procedure and testing location:			
<input type="checkbox"/>	CB Testing Laboratory:		
Testing location/ address			
Tested by (name + signature).....			
Approved by (name + signature)			
Testing procedure: CTF Stage 1			
Testing location/ address.....			
Tested by (name + signature).....			
Approved by (name + signature)			
Testing procedure: CTF Stage 2			
Testing location/ address.....			
Tested by (name + signature).....			
Witnessed by (name + signature).....			
Approved by (name + signature)			
<input checked="" type="checkbox"/>	Testing procedure: CTF Stage 3		
<input type="checkbox"/>	Testing procedure: CTF Stage 4		
Testing location/ address.....		TDK-LAMBDA UK LTD KINGSLEY AVE ILFRACOMBE EX34 8ES UNITED KINGDOM	
Tested by (name + signature).....		N. Marsh, M. Carter / Tester	
Witnessed by (name + signature).....		Hubert Koszewski / Witness	
Approved by (name + signature)		Tracy Burgess / Approver	
Supervised by (name + signature)		Robert Dmitruk / Reviewer	

List of Attachments (including a total number of pages in each attachment):

National Differences (30 pages)

Enclosures (355 pages)

Summary of testing:**Tests performed (name of test and test clause):**

STEADY FORCE TEST, 250 N (4.4.4.2, ANNEX T.5)

IMPACT TEST (4.4.4.4, ANNEX T.6)

CLASSIFICATION OF ELECTRICAL ENERGY SOURCES (5.2, 5.7)

DETERMINATION OF WORKING VOLTAGE (5.4.1.8)

BALL PRESSURE TEST (5.4.1.10.3)

SEPARABLE THIN SHEET MATERIAL (5.4.4.6.2)

ELECTRIC STRENGTH TEST (5.4.9)

SAFEGUARDS AGAINST CAPACITOR DISCHARGE AFTER DISCONNECTION OF A CONNECTOR (5.5.2.2)

RESISTANCE OF THE PROTECTIVE BONDING SYSTEM (5.6.6.2)

PROSPECTIVE TOUCH VOLTAGE AND TOUCH CURRENT MEASUREMENT (5.7)

INPUT TEST: SINGLE PHASE (B.2.5)

NORMAL OPERATING CONDITIONS TEMPERATURE MEASUREMENT (B.2.6)

SIMULATED ABNORMAL OPERATING CONDITIONS (B.3)

SIMULATED SINGLE FAULT CONDITIONS (B.4)

TRANSFORMER OVERLOAD (ANNEX G.5.3.3)

ALTERNATIVE LOCKED-ROTOR OVERLOAD TEST FOR D.C. MOTORS (ANNEX G.5.4.6.3)

LIMITED SHORT CIRCUIT TEST (ANNEX R.1, 5.6.4.1, 5.6.4.4, 5.6.5.1)

STEADY FORCE TEST, 10 N (ANNEX T.2, 5.4.2.6, 5.4.3.2, G.15.3.6)

Testing Location:

**CTF Stage 3: TDK-LAMBDA UK LTD
KINGSLEY AVE
ILFRACOMBE
EX34 8ES UNITED KINGDOM**

Summary of compliance with National Differences:

List of countries addressed: AU,NZ, JP, EU Group Differences, US,CA

The product fulfils the requirements of: EN 62368-1:2014 + A11:2017

Copy of Marking Plate - Refer to Enclosure titled Marking Plate for copy.

TEST ITEM PARTICULARS:	
Classification of use by	Skilled person
Supply Connection	AC Mains DC Mains
Supply % Tolerance	
Supply Connection – Type	mating connector
Considered current rating of protective device as part of building or equipment installation	20 A; building;
Equipment mobility	for building-in
Over voltage category (OVC)	OVC II
Class of equipment	Class I
Access location	N/A
Pollution degree (PD)	PD 2
Manufacturer’s specified maximum operating ambient (°C)	70°C (de-rated output power by 2.5% per °C above 50°C)
IP protection class	IPX0
Power Systems	TN
Altitude during operation (m)	5000 m
Altitude of test laboratory (m)	2000 m or less
Mass of equipment (kg)	3.6kg QM8, 3.2kg for QM7, 2.3kg for QM5 and 1.9/kg for the QM4
POSSIBLE TEST CASE VERDICTS:	
- test case does not apply to the test object..... :	N/A
- test object does meet the requirement :	P (Pass)
- test object does not meet the requirement :	F (Fail)
TESTING:	
Date of receipt of test item..... :	2017-05-25, 2017-06-30, 2017-07-13, 2017-07-24, 2017-09-05, 2018-04-27, 2018-09-12, 2018-10-10, 2018-10-15, 2018-10-23, 2018-10-25, 2018-11-06, 2018-11-13, 2018-11-19, 2018-11-20, 2018-11-23, 2018-11-28, 2018-11-30, 2018-12-06, 2018-12-17, 2018-12-18, 2019-01-08, 2019-01-18, 2019-01-22, 2019-01-30, 2019-02-05, 2019-02-11, 2019-02-18, 2019-03-05, 2019-03-07, 2019-03-11, 2019-03-26, 2019-04-01, 2019-04-04, 2019-04-05, 2019-04-09, 2019-04-18, 2019-04-23
Date (s) of performance of tests..... :	2018-04-17 to 2019-04-23
GENERAL REMARKS:	
<p>"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report.</p> <p>Throughout this report a <input type="checkbox"/> comma / <input checked="" type="checkbox"/> point is used as the decimal separator.</p>	

Manufacturer's Declaration per sub-clause 4.2.5 of IECEE 02:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies)	TDK-LAMBDA UK LTD KINGSLEY AVE ILFRACOMBE EX34 8ES UNITED KINGDOM PANYU TRIO MICROTRONICS CO LTD SHIJI INDUSTRIAL ESTATE DONGYONG NANSHA GUANGZHOU GUANGDONG 511453 CHINA
GENERAL PRODUCT INFORMATION:	
Report Summary	
All applicable tests according to the referenced standard(s) have been carried out.	
Product Description	
The QM or QS series of switch mode power supply consists of: Main board 1. Input filter, consisting of the input fuse(s), X and Y capacitors, common mode chokes up to the bridge. 2. PFC (boost circuit), consisting of the boost choke and associated switching FETs/circuitry. 3. Low power Standby circuit and Fan outputs consisting of the fly-back transformer and switching IC/circuitry supplying the Low Power Standby option and Fan outputs. 4. Secondary circuits, consisting of supply to the Low Power Standby output and fan supply. Modules 5. Forward converter situated on the module, consisting of the main transformer and switching FETs/circuitry. 6. Secondary circuits, consisting of Module output, CH1/2 good and inhibit/enable. Standby options 7. High power Standby circuit, consisting of the standby transformer and switching IC/circuitry supplying the High Power standby output. 8. Low power Standby circuit, supplied from the Main board. 9. Secondary circuits, consisting of High Power Standby output, Low Power Standby output, fan supply, AC fail and inhibit/enable. (See Model Differences for details of nomenclature)	
Model Differences	
See Enclosure 7-01.	

Additional application considerations – (Considerations used to test a component or sub-assembly) -

For best thermal performance and to ensure safety requirements are met at full load conditions, products are configured with modules starting from slot 1 in the following order:

1. Highest power SC modules
2. Lower power SC modules
3. Any other modules

Consult TDK-Lambda UK Ltd if a non-standard configuration is required.

Cooling for unit

Component temperatures for customer air cooled models, must be monitored in the end use application described in the "Cooling for Unit Temperature Table" below:

The following method must be used for determining the safe operation of PSUs.

The components listed in the following table must not exceed the temperatures given. To determine the component temperatures the heating tests must be conducted in accordance with the requirements of the standard in question. Consideration should also be given to the requirements of other safety standards. Test requirements include: PSU to be fitted in its end-use equipment and operated under the most adverse conditions permitted in the end-use equipment handbook/specification and which will result in the highest temperatures in the PSU. To determine the most adverse conditions consideration should be given to the end use equipment maximum operating ambient, the PSU loading and input voltage, ventilation, end use equipment orientation, the position of doors & covers, etc. Temperatures should be monitored using type K fine wire thermocouples (secured with cyanoacrylate adhesive, or similar) placed on the hottest part of the component (out of any direct airflow) and the equipment should be run until all temperatures have stabilised.

Cooling for unit temperature table (see layout drawings in handbook):

Cooling for unit temperature table:

Circuit Ref:	Description	Max. Temperature (°C)
PFC	-	-
QM7	-	-
L2	Common Mode Choke	115 (140)
L3	Boost choke	125
C2	Electrolytic Capacitors	71 (105)
C10	Electrolytic Capacitors	64 (105)
C7	Electrolytic Capacitors	64 (105)
C8	Electrolytic Capacitors	73 (105)
C11	Electrolytic Capacitors	77 (105)
C3, C14,	X Capacitor	100
C12	Y Capacitors	105
TX1	Fly back Transformer	120
D1	Diode bridge	114 (130)
D3	PFC diode	130
U4	Opto-coupler	100
U3	Voltage regulator	120 (130)
Q2	Boost FETS	130
QM5	-	-

L2	Common Mode Choke	115 (140)
L4	Boost choke	125
C2	Electrolytic Capacitors	71 (105)
C10	Electrolytic Capacitors	71 (105)
C7	Electrolytic Capacitors	64 (105)
C8	Electrolytic Capacitors	60 (105)
C11	Electrolytic Capacitors	77 (105)
C3, C14,	X Capacitor	100
C12	Y Capacitors	105
TX1	Fly back Transformer	120
D1	Diode bridge	118 (130)
D3	PFC diode	130
U4	Opto-coupler	100
U3	Voltage regulator	120 (130)
Q2	Boost FETS	130
QM8	-	-
L2	Common Mode Choke	115 (140)
L3	Boost choke	125
C2	Electrolytic Capacitors	71 (105)
C10	Electrolytic Capacitors	64 (105)
C7C	Electrolytic Capacitors	74 (105)
C8	Electrolytic Capacitors	73 (105)
C11	Electrolytic Capacitors	77 (105)
C3, C14,	X Capacitor	100
C12	Y Capacitors	105
TX1	Fly back Transformer	120
D1	Diode bridge	114 (130)
D3	PFC diode	130
U4	Opto-coupler	100
U3	Voltage regulator	120 (130)
Q2	Boost FETS	130
QM4	-	-
L2	Common Mode Choke	115 (140)
L3	Boost choke	125
C8	Electrolytic Capacitors	57 (105)
C10	Electrolytic Capacitors	71 (105)
C11	Electrolytic Capacitors	77 (105)
C5	X Capacitor	100
C12, C15	Y Capacitors	105
TX1	Fly back Transformer	120
D1	Diode bridge	118 (130)
D3	PFC diode	130
U3	Voltage regulator	120 (130)
Q1	Boost FET	130
Low Power Options	-	-
U6	Opto-couplers	100
High Power Options	-	-
C6	Electrolytic Capacitors	73 (105)

XU3	Opto-couplers	100
TX1	Transformer Class F	130
Q PMbus -	-	-
XU3	Opto-couplers	100
DM/DH Modules	-	-
C206	Y Capacitors	105
C207	Electrolytic Capacitors	84 (105)
U8	Opto-couplers	100
Q1	Primary FET	120 (130)
D201	Output diode	124 (130)
TX1	Transformer Class B	110
SC module Modules	-	-
C206	Electrolytic Capacitors	83 (105)
C209	Y Capacitors	105
U1	Opto-couplers	100
TX1	Transformer Class B	110
TX1 (12V)	Transformer Class F	130
Q1	Primary FET	127 (130)
Q203	Secondary FET	130
SB module Modules	-	-
C206	Electrolytic Capacitors	83 (105)
C209	Y Capacitors	105
U1	Opto-couplers	100
TX1	Transformer Class B	110
Q1	Primary FET	127 (130)
Q203	Secondary FET	130
SA module Modules	-	-
C202	Electrolytic Capacitors	76 (105)
C209	Y Capacitors	105
XU206	Opto-couplers	100
TX2	Transformer Class B	110
XQ1	Primary FET	130
XU202	Secondary FET	130

Higher temperature limits (in brackets) may be used but product life may be reduced.

Technical Considerations

- The product was submitted and evaluated for use at the maximum ambient temperature (T_{ma}) permitted by the manufacturer's specification of : 70°C, (65°C for QM5 option I), total output power and module output power de-rated 2.5% per °C above 50°C
- The product is intended for use on the following power systems : TN, IT (Norway only), TT
- The equipment disconnect device is considered to be : provided in the end product
- The following were investigated as part of the protective earthing/bonding : Printed wiring board trace (refer to Enclosure - Schematics + PWB for layouts)
- The following are available from the Applicant upon request : Installation (Safety) Instructions / Manual
- The product was investigated to the following additional standards : EN 62368-1:2014 + A11:2017

Engineering Conditions of Acceptability

When installed in an end-product, consideration must be given to the following:

- The following product-line tests are conducted for this product : Earthing Continuity
- The end-product Electric Strength Test is to be based upon a maximum working voltage of : Primary-Secondary: 457Vrms, 665Vpk, Primary-Earthed Dead Metal: 373Vrms, 680Vpk
- The following output circuits are at ES1 energy levels : see Model differences in Enclosure 7-01
- The following output circuits are at ES2 energy levels : see Model differences in Enclosure 7-01
- The following output circuits are at ES3 energy levels : see Model differences in Enclosure 7-01
- The following output circuits are at PS3 energy levels : all circuits
- The maximum investigated branch circuit rating is : 20 A
- The investigated Pollution Degree is : 2
- Proper bonding to the end-product main protective earthing termination is : Required
- An investigation of the protective bonding terminals has : been conducted
- The following end-product enclosures are required : Mechanical, Fire, Electrical (excluding QM5 option I, non-customer air version, front end)
- The following magnetic devices (e.g. transformers or inductor) are provided with an OBJY2 insulation system with the indicated rating greater than Class A (105°C) : examples: T2 (Class B) or L1 (155°C), examples: T2 (Class B) or L1 (155°C), examples: T2 (Class B) or L1 (155°C), PFC : TX1 Class F, MODULES: TX1 (TX2 for SA modules) Class B except 12V SC Module TX1 Class F. GLOBAL OPTIONS/PMBUS: TX1 Class F. See Critical Components Table for details of insulation systems used.
- Fans: The fan provided in this sub-assembly is not intended for operator access.
- All models require component temperatures to be monitored as detailed in the additional information.
- Model KQM5001V-x is a customer air model and due consideration to the cooling in end equipment as described in the Additional Information section must be applied.
- TS3 metal chassis/enclosure accessible to skilled person, skilled safeguard to be considered in the end-product.