



DECLARATION OF CONFORMITY  
iAC SERIES

**TDK-Lambda Americas Inc.**  
**Dallas Technical Center (DTC)**  
 3320 Matrix Drive, Ste 100, Richardson, TX 75082  
 Phone (214) 239-3100 FAX (214) 239-3102  
 www.tdk-lambda.com

We TDK-Lambda Americas Inc. declare under our sole responsibility that the iAC series of Product as detailed on the attached products covered sheet or below, comply with the provisions of the following European directives and are eligible to bear the CE mark.

Low Voltage                      Directive 2006/95/EC (until 19 April 2016)  
     Directive 2014/35/EU (from 20 April 2016)  
 RoHS 2                                Directive 2011/65/EU (8 June 2011)

Assurance of conformance of the described product with the provisions of the stated EC Directive is given through compliance to the following standards:



DIN EN 60950-1 (VDE 0805-1):2014-08  
 EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011+A2:2013  
**IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013**

*The VDE Testing and Certification Institute (EU Identification No.0366), Merianstr. 28, 63069 Offenbach(Germany), has tested and certified the product.*

*Last two digits of the year in which the CE marking was affixed:16*

*Certificate No. 40015516  
 File Reference 2520400-3336-0013 / 221868*

Our European Representative in the EU is TDK-Lambda UK Limited, Kingsley Avenue, Ilfracombe, Devon, EX34 8ES, UK. Further, all products covered by this declaration are manufactured in accordance with ISO9000:2008.

Richardson, Texas 03/11/2016 (Place, Date)		Quality Engineer (Legally binding signature of the issuer)
Richardson, Texas 03/11/2016 (Place, Date)		Product Safety Engineer (Legally binding signature of the issuer)

PRODUCT COVERED SHEET

Product Designation

The Metamere iAC product family consists of high density non-isolated DC-DC power modules intended to be purchased and used as a component in an end-user's power system. The modules currently come in one input voltage range; a wide range 6 – 14.4Vdc input. The output voltage will be between 0.7525V and 5.0V depending upon the model number.

MODEL #	Input Voltage*	Max Input Current**	Output Voltage***	Output Current	Max. Output Power
iAC12***A%%V -0##	6.0-14.4 (1)	18 (2)	<b>(3)</b>	<b>(4)</b>	80W (5)
iAC12016A008V-0##	6.0-14.4	18	0.7525	16	80W
iAC12016A012V-0##	6.0-14.4	5	1.2	16	19.2W
iAC12016A015V-0##	6.0-14.4	6	1.5	16	24W
iAC12016A018V-0##	6.0-14.4	7	1.8	16	28.8W
iAC12016A020V-0##	6.0-14.4	8	2	16	32W
iAC12016A025V-0##	6.0-14.4	9.5	2.5	16	40W
iAC12016A033V-0##	6.0-14.4	12	3.3	16	52.8W
iAC12016A050V-0##	6.0-14.4	18	5	16	80W
iAC12010A008V-0##	6.0-14.4	11	0.7525	10	50W
iAC12010A012V-0##	6.0-14.4	3	1.2	10	12W
iAC12010A015V-0##	6.0-14.4	4	1.5	10	15W
iAC12010A018V-0##	6.0-14.4	4.5	1.8	10	18W

where:

1) Shows maximum input range. Some products may offer an optional narrow input voltage range, such as 9.6V to 14V. This option will be differentiated with the ## placeholder.

2) Maximum input current will be a data sheet parameter telling the customer the maximum current the power module will draw from 0Vin to Vin,max. The typical current draw will be significantly lower. Fuse value for testing shall be as specified in the product data sheet.

3) %%% represents rated nominal output voltage between .7525V (008) and 5V (050). Except for the wide trim version (see below), the output voltage will be adjustable by the customer over a range of +10% to -75% of the rated nominal output voltage. When the output voltage is adjusted up the maximum output power is fixed (i.e. maximum output current is decreased). When the output voltage is adjusted down, the maximum output current may increase (but the available output power will be the same or lower). The 008V option has a wide output voltage adjustment range and can be trimmed up to 5.5

4) \*\*\* represents rated maximum output current between 1A (001) and 16A (016)

5) Total output power is less than or equal to 80W