



**TDK-Lambda Ltd.**  
Haharoshet St. 56  
Industrial Zone P.O.B.  
500  
Karmiel, Israel  
Tel: 972-(0)4-9887491  
Fax: 972-(0)4-9583071  
www.tdk-lambda.co.il

## EU DECLARATION OF CONFORMITY

### Z+ Series

We, TDK-Lambda Ltd, of Haharoshet St. 56 Industrial Zone P.O.B. 500 Karmiel, Israel declare under our sole responsibility that the TDK-Lambda Z200, Z400, Z600 and Z800 series of power supplies, as detailed on the attached products covered sheet, complies with the provisions of the following European Directives and is eligible to bear the CE mark:

|                       |                                     |
|-----------------------|-------------------------------------|
| Low Voltage Directive | 2014/35/EU                          |
| EMC Directive         | 2014/30/EU                          |
| RoHS Directive        | 2011/65/EU (as amended by 2015/863) |

Assurance of conformance of the described product with the provisions of the stated EC Directives is given through compliance to the following standards:

|                                     |                 |
|-------------------------------------|-----------------|
| Electrical Safety (LVD)             | EN 61010-1:2010 |
| Electromagnetic Compatibility (EMC) | EN 61326-1:2013 |

Our European Representative in the EU is TDK-Lambda Germany GmbH, located at Karl-Bold-Str. 40, D-77855 Achern, Germany.

|                                   |   |
|-----------------------------------|---|
| Name of Authorized Signatory      | Christopher Haas  |
| Signature of Authorized Signatory |  |
| Position of Authorized Signatory  | Head of Quality & Compliance,<br>TDK-Lambda Germany GmbH                            |
| Date                              | 27 December 2019  |
| Date when first CE marked         | 22 March 2012   |
| Place where signed                | Achern, Germany   |

## PRODUCTS COVERED SHEET: Z+ SERIES

1. Z200 series;
2. Z400 series;
3. Z600 series;
4. Z800 series

Configuration code: Zxxx-yyy-o-p-w-m

where

xxx=any number between 010 to 650;

yyy=any number between 0.32 to 72;

o=blank or (in any combination) L, L2, IEEE, IS420, IS510, LAN;

p=blank or E, I, J or U;

w=blank or CO;

m=blank or A-Z, 0-9, (not safety relevant options).