Alimentation rail-DIN – 1-Ph

DRB 0.63 / 1.25 / 2.1 / 4.2 A

TDK·Lambda

Points clés produit

- Dimensions ultra compactes laissant plus d'espace sur le rail-DIN
- Rendement jusqu'à 91%
- Conforme à l'ErP (éco conception)
- Coût optimisé

Caractéristiques principales

- Versions 15 / 30 / 50 / 100W
- Tensions de sortie 5, 12-15, 24, 48Vdc
- CEM: Classe B en conduit & rayonné
- Pleine puissance jusqu'à 55°C (70°C pour la 15W)
- Refroidissement par convection
- Plage de Tension d'entrée 85-265Vac

Applications typiques

- Automatismes Industriels
- Contrôle de processus, Machines CNC
- Dispositifs de manutention et d'emballage
- Industrie chimique, Robotique
- Test and mesure
- Machines industrielles d'impression

Product Highlights

- Ultracompact footprint saves space on DIN-Rail
- Efficiency up to 91%
- ErP compliant (eco design)
- Cost optimized

Key Specifications

- 15 / 30 / 50 / 100 W versions
- Output voltages 5, 12-15, 24, 48Vdc
- Class B EMI
- Full load up to 55°C (70°C 15W)
- Convection cooled
- 85-265Vac Input

Typical Applications

- Factory automation
- Process control, NC machines
- Material handling and packaging equipment
- Chemical processing, robotic automation
- Test and measurement
- Industrial printing machines

For more information about TDK-Lambda: www.emea.tdk-lambda.com