



**TDK-Lambda Corporation**  
2-5-1, Nihonbashi  
Chuo-ku, Tokyo  
103-6128 Japan  
www.tdk-lambda.com

## EU DECLARATION OF CONFORMITY

CC-E series

We, TDK-Lambda Corporation, of 2-5-1, Nihonbashi, Chuo-ku, Tokyo, 103-6128 Japan, declare under our sole responsibility that the TDK-Lambda power supplies, as detailed on the attached products covered sheets, complies with the provisions of the following European Directives and is eligible to bear the CE mark:

Low Voltage	Directive 2014/35/EU
RoHS 10	Directive 2011/65/EU (as amended by 2015/863)

Assurance of conformance of the described product with the provisions of the stated EC Directive is given through compliance to the following standards:

Electrical Safety (LVD)	EN 60950-1:2006 + A2:2013
-------------------------	---------------------------

Our representative in the EU is TDK-Lambda Germany GmbH, located at Karl-Bold-Str. 40, 77855 Achern, Germany.

Name of Authorized Signatory:	Christopher Haas
Signature of Authorized Signatory:	
Position of Authorized Signatory:	Head of Quality & Compliance, TDK-Lambda Germany GmbH
Date:	14 <sup>th</sup> August 2019
Date when first CE marked:	1 <sup>st</sup> January 2013
Place where signed:	Achern, Germany

**The products covered by this declaration are (see next pages):**

### CC1R5-05-E, CC1R5-12-E, CC1R5-24-E and CC1R5-48-E series

Example product nomenclature:

Series	Output (W) [range]	Rated input (V) [voltage range]	Output (V) [range]	Number of outputs	Terminal construction	Variation	Control number
I	II	III	IV	V	VI	VII	VIII
CC	1R5-	24	05	S	F	-	-E

- I. Series Type: CC
- II. Output wattage:  
1R5-: [1.32, 1.44 or 1.50W]
- III. Input rated voltage:  
05: [4.5-9V], 12: [9-18V], 24: [18-36V], 48: [26-76V]
- IV. Output Voltage:  
03: [3.3-3.6V], 05: [5.0-6.0V], 12: [12-15V (for 1 output type) to +/-12+/-15 (for 2 output types)]
- V. Output number:  
S: 1 output, D: 2 outputs
- VI. Terminal construction:  
F: Flow (DIP) type, R: Reflow (SMD) type
- VII. Variation:  
Blank: Standard, A-Z: Variation
- VIII. Internal Control Number  
-E: The fifth generation

### CC3-05-E, CC3-12-E, CC3-24-E and CC3-48-E series

Example product nomenclature:

Series	Output (W) [range]	Rated input (V) [voltage range]	Output (V) [range]	Number of outputs	Terminal construction	Variation	Control number
I	II	III	IV	V	VI	VII	VIII
CC	3-	24	05	S	F	-	-E

- I. Series Type: CC
- II. Output wattage:  
3-: [2.64 or 3.00W]
- III. Input rated voltage:  
05: [4.5-9V], 12: [9-18V], 24: [18-36V], 48: [36-76V]
- IV. Output Voltage:  
03: [3.3-3.6V, for model of SIP type: 3.3-3.67V], 05: [5.0-6.0V], 12: [12-15V (for 1 output type) or +/-12 to +/-15 (for 2 output type)]
- V. Output number:  
S: 1 output, D: 2 outputs
- VI. Terminal construction:  
F: Flow (DIP) type, R: Reflow (SMD) type, S: SIP models
- VII. Variation:  
Blank: Standard, A-Z: Variation
- VIII. Internal Control Number  
-E: The fifth generation

### CC6-05-E, CC6-12-E, CC6-24-E and CC6-48-E series

Example product nomenclature:

Series	Output (W) [range]	Rated input (V) [voltage range]	Output (V) [range]	Number of outputs	Terminal construction	Variation	Control number
I	II	III	IV	V	VI	VII	VIII
CC	6-	24	05	S	F	-	-E

- I. Series Type: CC
- II. Output wattage:  
6-: [3.96, 4.95, 5.00 or 6.00W]
- III. Input rated voltage:  
05: [4.5-9V], 12: [9-18V], 24: [18-36V], 48: [36-76V]
- IV. Output Voltage:  
03: [3.3-3.6V], 05: [5.0-6.0V], 12: [12-15V (for 1 output type) to +/-15 (for 2 output types)]
- V. Output number:  
S: 1 output, D: 2 outputs
- VI. Terminal construction:  
F: Flow (DIP) type, R: Reflow (SMD) type
- VII. Variation:  
Blank: Standard, A-Z: Variation
- VIII. Internal Control Number  
-E: The fifth generation

### CC10-05-E, CC10-12-E, CC10-24-E and CC10-48-E series

Example product nomenclature:

Series	Rated input (V) [voltage range]	Output (V) [range]	Number of outputs	Terminal construction	Variation	Control number
I	II	III	IV	V	VI	VII
CC10-	05	03	S	F	-	-E

- I. Series Type: CC10-
- II. Input rated voltage:  
05: [4.5-9V], 12: [9-18V], 24: [18-36V], 48: [36-76V]
- III. Output Voltage:  
03: [3.3-3.6V], 05: [5.0-6.0V], 12: [12-15V]
- IV. Output number:  
S: 1 output, D: 2 outputs
- V. Terminal construction:  
F: Flow (DIP) type, R: Reflow (SMD) type
- VI. Variation:  
Blank: Standard, A-Z: Variation
- VII. Internal Control Number  
-E: The fifth generation

### CC15-24-E series

Example product nomenclature:

Series	Output (W) [range]	Rated input (V) [voltage range]	Output (V) [range]	Number of outputs	Terminal construction	Variation	Control number
I	II	III	IV	V	VI	VII	VIII
CC	15-	24	05	S	F	A	-E

- I. Series Type: CC
- II. Output wattage:  
15-: [15W]
- III. Input rated voltage:  
24: [18-36V]
- IV. Output Voltage:  
03: [3.3V], 05: [5.0V]
- V. Output number:  
S: 1 output
- VI. Terminal construction:  
F: Flow type (DIP), R: Reflow type (SMD)
- VII. Internal Control Number (Optional):  
A: A-Z or Blank
- VIII. Internal Control Number  
-E: A-Z or Blank

### CC15-P-E series

Example product nomenclature:

Series	Output (W)	Rated input (V) [voltage range]	Output (V) [range]	Number of outputs	Terminal construction	Case	Identification	Control number
I	II	III	IV	V	VI	VII	VIII	IX
CC	15-	24	3	S	F	P	#	-E

- I. Series Type: CC
- II. Output wattage:  
15-: [15W]
- III. Input rated voltage:  
24: [18 – 36V], 48: [36 – 76V]
- IV. Output Voltage:  
03, 3R3, 3.3 : 3.3V; 05, 5R0, 5.0 : 5.0V; 12, 12R: 12.0V; 15, 15R: 15.0V
- V. Output number:  
S: 1 output
- VI. Terminal construction:  
F: Flow type (DIP), R: Reflow type (SMD)
- VII. Case:  
P: with case, H: without case
- VIII. Identification  
Blank: Standard, A – Z: Identification for sales to manufacturer
- IX. Internal control number not affecting safety  
-E: The fifth generation

### CC25-24-E series

Example product nomenclature:

Series	Output (W) [range]	Rated input (V) [voltage range]	Output (V) [range]	Number of outputs	Terminal construction	Variation	Control number
I	II	III	IV	V	VI	VII	VIII
CC	25-	24	05	S	F	A	-E

- I. Series Type: CC
- II. Output wattage:  
25-: [25W]
- III. Input rated voltage:  
24: [18-36V]
- IV. Output Voltage:  
03: [3.3V], 05: [5.0V]
- V. Output number:  
S: 1 output
- VI. Terminal construction:  
F: Flow (DIP) type, R: Reflow (SMD)
- VII. Internal Control Number (Optional):  
A: A-Z or Blank
- VIII. Internal Control Number  
-E: A-Z or Blank

### CC30-P-E series

Example product nomenclature:

Series	Output (W)	Rated input (V) [voltage range]	Output (V) [range]	Number of outputs	Terminal construction	Case	Identification	Control number
I	II	III	IV	V	VI	VII	VIII	IX
CC	30-	24	3	S	F	P	#	-E

- IV. Series Type: CC
- V. Output wattage:  
30-: [30W]
- VI. Input rated voltage:  
24: [18 – 36V], 48: [36 – 76V]
- IV. Output Voltage:  
03, 3R3, 3.3: 3.3V; 05, 5R0, 5.0: 5.0V; 12, 12R: 12.0V; 15, 15R: 15.0V
- X. Output number:  
S: 1 output
- XI. Terminal construction:  
F: Flow type (DIP), R: Reflow type (SMD)
- XII. Case:  
P: with case, H: without case
- XIII. Identification  
Blank: Standard, A – Z: Identification for sales to manufacturer
- XIV. Internal control number not affecting safety  
-E: The fifth generation