

180-200W Configurable Medical power supply.

Features	Benefits
• High efficiency	Minimises heat in system
• Low profile	Fits 1U applications
• Low earth leakage and Class B EMC	Simplifies system design, reduces cost
• 2 x MOPPs isolation	Simplifies system design
• 3 year warranty	Low cost of ownership



Input			
Input Voltage	90-264Vac (100 - 240Vac nominal)	Input Frequency	45 - 63Hz
Input Harmonics	EN61000-3-2 compliant	Inrush Current	<40A at 25°C and 230Vac (cold start)
Input Fuse	Fast acting (not user accessible)		
Earth Leakage Current	123µA at 120Vac (60Hz), 257µA max at 240Vac (60Hz) Worst case leakage current is less than 300µA at 264Vac, 63Hz (normal condition, 0.5mA Single Fault Condition) Lower leakage versions available, contact sales office for details		

Isolation			
Input to Output	2 x MOPPs (3rd edition 60601) 4kVac	type tested to 4kVac (equivalent to 5.7kVdc), production tested to 4.3kVdc	
Input to Earth	1 x MOOP (3rd edition 60601) 1.5kVac, 2.3kVdc	Output to Earth	200Vdc

QUICK SELECTOR - example configurations				Additional variants available, see "How to Create a Product Description"
Model	Ch1	Ch3	Ch4	
NV1-1T000-M	12V / 15A	-	-	
NV1-1G000-M	24V / 7.5A	-	-	
NV1-3G0TT-M	24V / 7.5A	12V / 5A	-12V / 1A	
NV1-3G0FF-M	24V / 7.5A	15V / 5A	-15V / 1A	

How To Create A Product Description

Confirm availability of created product with TDK-Lambda

NV1-	#o/p	Ch1	0	Ch3 ₂	Ch4 ₃	Case Option	-M	Connector Option
------	------	-----	---	------------------	------------------	-------------	----	------------------

Number of outputs

Ch1, Ch3, Ch4 Letter / number from 'Available Outputs' table to represent output voltage

Blank standard, vertical connector
R Right angled connector (see handbook for 'R' connection and mechanical details)

Medical with 4kVac (2 x MOPPs) input to output isolation

Blank no case
-C U chassis + cover
-U U chassis
-F End fan + case₁
-I End fan + case + IEC inlet₁

- Needs 0H, 3H, 5H, TH or FH type channel 4. The fan speed is temperature dependent, ensuring optimum cooling and lowest audible noise.
- For negative output channel 3, follow chosen letter by 'Y'. For example, TY channel 3 = -12V / 5A.
- For positive output channel 4, follow chosen letter by 'P'. For example, TP channel 4 = +12V / 1A.

Available Outputs		Other output options are available, please contact sales office with your requirements				
Channel 1	Adjustment Range	Channel 2	Channel 3 ₁	Adjustment Range	Channel 4 ₂	Adjustment Range
T 12V / 15A F 15V / 12A	12 - 15V ₃ 12 - 15V ₄	Not available	T 12V / 5A F 15V / 5A G 24V / 2.5A O Omit	12 - 15V 12 - 15V 18 - 24V	T -12V / 1A F -15V / 1A 3HP +3.3V / 2A ₆ 5HP +5V / 2A ₆ TH -12V / 2A ₆ FH -15V / 2A ₆ OH Fan supply only O Omit	Fixed Fixed Fixed Fixed Fixed Fixed
G 24V / 7.5A	24 - 28V ₅					

1. Follow letters in red by 'Y' for negative output channel 3. 3. 12 - 12.5V if 24V channel 3 fitted. 5. 24 - 26V if 24V channel 3 fitted.
 2. Follow letters in red by 'P' for positive output channel 4. 4. 14.5 - 15V if 24V channel 3 fitted. 6. 1.5A max with '-F' or '-I' option.

Output Specification		
Turn on time	1.5s max	at 90Vac and 100% rated output power
Efficiency	up to 90%	configuration dependent
Hold up	16ms min	at 90Vac
Ripple and Noise	<1%	(or 50mV if higher) pk-pk, using EIAJ test method & 20MHz bandwidth
Voltage Accuracy	±1%	±4% for Channel 4 with 'T' or 'F' type outputs, +4/-3% for all other channel 4.
Remote Sense	Yes	Channel 1. Max 0.5V total line drop
Minimum Load	No	on any output
Total Regulation	1% (or 50mV if greater)	Including Line (for 90-264Vac input change), Load (for 0-100% load change) and Cross (for 0-100% load change on any other output) regulation.
Transient Response	<4%	of set voltage for 50% load change (in 50µs within the range 25-100% load)
Recovery	500µs	for recovery to 1% of set voltage
Over Voltage Protection	Yes	See Application Notes for details
Short Circuit Protection	Yes	
Over Temperature Protection	Yes	
Peak Output Power	200W	Single output units with 12V, 15V or 24V (T, F or G). Average output power must not exceed 180W over any 5 minute period
Ch1 Good Signal	Yes	Provides a Logic 'Low' signal after Channel 1 output is within 90% (±5%) of nominal

Environment	
Temperature	0°C to 50°C operational, -40°C to 70°C storage (max 12 months). Full load, with either '-F' option fitted or 2m/s air blown from input to output (approximately 10CFM)
Derating	50°C to 65°C derate each output by 2.5% per °C
Low Temp Startup	-20°C
Humidity	5 - 95% RH non condensing
Shock	±3 x 30g shocks in each plane, total 18 shocks 30g shock = 11ms (+/-0.5msec), half sine Conforms to EN60068-2-27, EN60068-2-47, IEC68-2-27, IEC68-2-47, JIS C0041-1987. Conforms to MIL-STD-810E/F, Method 516.5, Pro I, IV, VI
Vibration	Single axis 10 - 500 Hz at 2g (sweep and endurance at resonance) in all 3 planes Conforms to EN60068-2-6, IEC68-2-6 Conforms to MIL-STD-810E, Method 514.4, Pro I, Cat 1,9
Altitude	3000 metres operational (4000m for NV1-1G000-M for 60601-1 3rd edition)
Pollution	Degree 2, Material group IIIb

Immunity EN61000-6-2:2005, EN60601-1-2:2007				Criteria
Electrostatic Discharge	EN61000-4-2	Level 4	Air discharge 15kV, Contact discharge 8kV. Not applicable to open frame units	A
Electromagnetic Field	EN61000-4-3	Level 3	12V/m	A
Fast / Burst Transient	EN61000-4-4	Level 4	ac input tested to 4.4kV dc output tested to 2.2kV	A
Surge Immunity	EN61000-4-5	Level 3	Common mode - 2.2kV, Differential - 1.1kV	A
Conducted RF Immunity	EN61000-4-6	Level 3	12V	A
Power Frequency Magnetic Field	EN61000-4-8	Level 4	30A/m	A
Voltage Dips, Variations, Interruptions	EN61000-4-11	Class 3	Criteria B for 5 sec interruption and dips to 40% for 5 cycles below 154Vac nominal input	A

Emissions EN61000-6-3:2007, EN60601-1-2:2007		
Radiated Electric Field	EN55011, EN55032	(as per CISPR.11/22) Class B, FCC47 part 15 subpart B see application note for details. Additional filtering required for IEC inlet version.
Conducted Emissions	EN55011, EN55032	(as per CISPR.11/22) Class B, FCC47 part 15 subpart B
Conducted Harmonics	EN61000-3-2	Class A
Flicker	EN61000-3-3	Compliant - d _{max} only

Approvals / Accreditations

IEC/EN 62368-1, UL62368-1 / CSA 22.2 No 62368-1
 IEC/EN 60950-1, UL60950-1 / CSA 22.2 No 60950-1
 IEC/EN 60601-1, UL/CSA 60601-1, ANSI/AAMI ES60601-1
 CAN/CSA-C22.2 No 60601-1-08
 IEC/EN61010

CE Mark (EN62368-1)

CB certificate and Report available on request

Designed and manufactured under the control of ISO9001 and ISO13485 (including risk management).

Notes

File E135494


File E135494

File E349607

Designed to meet

Low Voltage Directive (LVD), electromagnetic compatibility (EMC) and Restriction of Hazardous Substances (RoHS)

Please check with technical sales for status of approvals



Mating Parts (Molex or Equivalent)


Conn	Housing	Pins
J1	39-01-2245	45750-3112
J2	09-50-8051	08-52-0113

J1		J1	
PIN	FUNCTION	PIN	FUNCTION
12	STANDBY +Ve	24	Do not connect
11	Do not connect	23	Do not connect
10	CH1 OUTPUT	22	CH1 GOOD
9	CH1 OUTPUT	21	CH1 OUTPUT
8	CH1 OUTPUT	20	CH1 OUTPUT
7	+SENSE CH1	19	-SENSE CH1
6	0V COMMON	18	0V COMMON
5	0V COMMON	17	0V COMMON
4	Do not connect	16	0V COMMON
3	Do not connect	15	Do not connect
2	Do not connect	14	Do not connect
1	CH3 OUTPUT	13	CH4 OUTPUT

J2	
PIN	FUNCTION
1	EARTH
2	NOT CONNECTED
3	LIVE
4	NOT CONNECTED
5	NEUTRAL

Input and output connectors are not included with the product. They are available from TDK-Lambda

Part No	Contents
94910	1 off input connector and 3 crimps
94668	1 off output connector and 20 crimps



Notes: 1. All customer fixings M3

2. Maximum thread penetration 4.5mm

3. Maximum torque 0.9Nm

4. All tolerances +/-0.5mm



TDK-Lambda France SAS

Tel: +33 1 60 12 71 65
france@fr.tdk-lambda.com
www.emea.lambda.tdk.com/fr



Italy Sales Office

Tel: +39 02 61 29 38 63
info.italia@it.tdk-lambda.com
www.emea.lambda.tdk.com/it



Netherlands

info@nl.tdk-lambda.com
www.emea.lambda.tdk.com/nl



TDK-Lambda Germany GmbH

Tel: +49 7841 666 0
info.germany@de.tdk-lambda.com
www.emea.lambda.tdk.com/de



Austria Sales Office

Tel: +43 2256 655 84
info@at.tdk-lambda.com
www.emea.lambda.tdk.com/at




Switzerland Sales Office

Tel: +41 44 850 53 53
info@ch.tdk-lambda.com
www.emea.lambda.tdk.com/ch



Nordic Sales Office

Tel: +45 8853 8086
info@dk.tdk-lambda.com
www.emea.lambda.tdk.com/dk



TDK-Lambda UK Ltd.

Tel: +44 (0) 12 71 85 66 66
powersolutions@uk.tdk-lambda.com
www.emea.lambda.tdk.com/uk



TDK-Lambda Ltd.

Tel: +9 723 902 4333
info@tdk-lambda.co.il
www.emea.lambda.tdk.com/il



C.I.S.

Commercial Support:

Tel: +7 (495) 665 2627

Technical Support:

Tel: +7 (812) 658 0463

info@tdk-lambda.ru

www.emea.lambda.tdk.com/ru



TDK-Lambda Americas

Tel: +1 800-LAMBDA-4 or 1-800-526-2324
powersolutions@us.tdk-lambda.com
www.us.lambda.tdk.com



TDK Electronics do Brasil Ltda

Tel: +55 11 3289-9599
sales.br@tdk-electronics.tdk.com
www.tdk-electronics.tdk.com/en



TDK-Lambda Corporation

Tel: +81-3-6778-1113
www.jp.lambda.tdk.com



TDK-Lambda (China) Electronics Co. Ltd.

Tel: +86 21 6485-0777
powersolutions@cn.tdk-lambda.com
www.lambda.tdk.com.cn



TDK-Lambda Singapore Pte Ltd.

Tel: +65 6251 7211
tfs.mkt@sg.tdk-lambda.com
www.sg.lambda.tdk.com



TDK India Private Limited, Power Supply Division

Tel: +91 80 4039-0660
mathew.philip@in.tdk-lambda.com
www.sg.lambda.tdk.com

