

US-34826-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)

CB TEST CERTIFICATE

Product DC-To-DC Converters

Name and address of the applicant TDK-LAMBDA AMERICAS INC

SUITE 100

3320 MATRIX DR

RICHARDSON, TX 75082 USA

Name and address of the manufacturer TDK-LAMBDA AMERICAS INC

> SUITE 100 3320 MATRIX DR

RICHARDSON, TX 75082 USA

Name and address of the factory TDK-LAMBDA AMERICAS INC

SUITE 100 Note: When more than one factory, please report on page 2 3320 MATRIX DR

RICHARDSON, TX 75082 USA Additional Information on page 2

Ratings and principal characteristics Optional

Rated Input: 36 VDC Max, 23 A Max

Rated output: 48 VDC Max, 28 A Max, 150 W Max.

TDK or TDK-Lambda Trademark / Brand (if any)

®TDK

Type of Customer's Testing Facility (CTF) Stage used CTF Stage 2

Model / Type Ref. GQA24***A%%%V-xxx -R, GQA2W***A%%%V-xxx-R

See Page 2

Additional information (if necessary may also be

reported on page 2)

Additionally evaluated to EN 62368-1:2014 / A11: 2017; National

Differences specified in the CB Test Report.

Additional Information on page 2

A sample of the product was tested and found

to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part

of this Certificate

E220248-A6010-CB-1 issued on 2019-11-25

This CB Test Certificate is issued by the National Certification Body



Date: 2019-12-10

UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

folaska fly love

For full legal entity names see www.ul.com/ncbnames

Signature:

Jolanta M. Wroblewska



US-34826-UL

Model Details:

GQA2W***A%%%V-xxx-R, (PR); -R indicating RoHS compliance, or -(007) for unpotted or (-0P7) for potted.

Where

- 2W represents nominal input voltage, with a 9 36 Vdc input, with a Max Input Current of 23 A
- *** represents rated output current between 4.28 A 28 A; *** maybe 1 to 3 digits, note that last digit is preceded by decimal point.
- %%% represents rated output voltage between, 5 Vdc -28 Vdc, with Max Output Power of 150 W. Note that the third digit is preceded by a

decimal point. Example 120 implies 12.0 Volts. with Max Output Power of 120 W.

- xxx represents alphanumeric characters which indicates non safety related feature set options
- Optional -R indicating RoHS compliance, or (-007) for unpotted, or (-0P7) for potted)

GQA24***A%%%V-xxx -R (PR); -R indicating RoHS compliance, or -(007) for unpotted or (-0P7) for potted.

Where:

- 24 represents nominal input voltage, with a 18-36 Vdc input, Max Input Current 9 A dc;
- *** represents rated output current between 0 A 2.5 A, *** maybe 1 to 3 digits, note that last digit is preceded by decimal point.
- %%% represents rated output voltage, 48 Vdc nominal, Note that the third digit is preceded by a decimal point. Example 120 implies 12.0

Volts. with Max Output Power of 120 W

- xxx represents alphanumeric characters which indicates non safety related feature set options
- Optional -R indicating RoHS compliance, or (-007) for unpotted, or (-0P7) for potted)

Factories

TDK-LAMBDA MALAYSIA SDN BHD PLO33 KAWASAN PERINDUSTRIAN SENAI SENAI, 81400 JOHOR Malaysia

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-12-10

Signature:

Jolanta M. Wroblewska