Z+200 H.V Series

EVALUATION DATA

DWG No.: IA779-53-02		
APPD	CHK	DWG
22/6/14	Karmi S. June-19-14	Bar B. 19/6/14

TDK-Lambda

INDEX

	PAGE
1. EVALUATION METHOD	
1.1 Circuit used for determination	T-1~4
(1) Steady state data	
(2) Warm up voltage drift characteristics	
(3) Warm up current drift characteristics	
(4) Over voltage protection (OVP) characteristics	
(5) Output voltage rise/fall characteristics	
(6) Output current rise/fall characteristics	
(7) Dynamic line voltage and current response characteristics	
(8) Dynamic load voltage and current response characteristics	
(9) Response to brown-out characteristics	
(10) Inrush current characteristics	
(11) Leakage current characteristics	
(12) Output Voltage ripple & noise waveform 160V to 650V models	
(13) Output Current ripple & noise waveform 160V to 650V models	
1.2 List of equipment used	T-5
2. CHARACTERISTICS	
2.1 Steady state data	
(1) Regulation - Line & Load, Temperature drift	T-06~09
(2) Output voltage and ripple voltage v.s input voltage	T-10~11
(3) Output current and ripple current v.s input voltage	
(4) Efficiency and Input current vs. Output current	T-12~13
2.2 Warm up voltage drift & temperature stability	T-14~15
2.3 Over voltage protection (OVP) characteristics	T-16
2.4 ON/OFF Output rise characteristics	T-17~20
2.5 ON/OFF Output fall characteristics	T-21~24
2.6 Hold up time characteristics	T-25~26
2.7 Dynamic line response characteristics	T-27~30
2.8 Dynamic load response characteristics	T-31~33
2.9 Response to brown-out characteristics	T-34~37
2.10 Inrush current characteristics	T-38~39
2.11 Inrush current waveform	T-40~43
2.12 Input current waveform	T-44~45
2.13 Leakage current characteristics	T-46
2.14 Output voltage ripple & noise waveform	T-47

TERMINOLOGY USED

Definition

Vin	Input voltage
Vout	Output voltage
Iin	Input current
Iout	Output current
Ta	Ambient temperature
f	Frequency
C.V	Constant voltage mode
C.C	Constant current mode

1. EVALUATION METHOD

1.1 Circuit used for determination

(1) Steady state data

(2) Warm up voltage drift characteristics same as Steady state data

(3) Warm up current drift characteristics same as Steady state data

(4) Over voltage protection (OVP) characteristics

(5) Output voltage rise/fall characteristics same as Steady state data

(6) Output current rise/fall characteristics

1.1 Circuit used for determination

(7) Dynamic line voltage and current response characteristics

(8) Dynamic load voltage and current response characteristics

Constant Voltage mode

Output current waveform
Iout 0% <---> 100%

Output current waveform
Iout 50% <---> 100%

1.1 Circuit used for determination

(9) Response to brown-out characteristics

(10) Inrush current characteristics same as Response to brown-out

(11) Leakage current characteristics

(12) Output Voltage ripple & noise waveform 160V up to 650V models

(a) Normal mode (JEITA Standard RC-9131A)

1.1 Circuit used for determination

(12) Output Voltage ripple & noise waveform 160V up to 650V models

(b) Normal + Common mode

(13) Output Current rms ripple 160V to 650V models

Notes:
(*) Ouput Current rms ripple = Output Voltage rms ripple divided by the Load resistance.

1.2 List of equipment used

	EQUIPMENT USED	MANUFACTURER	MODEL No.
1	Digital oscilloscope	YOKOGAWA	DL1740 E/EL
2	Digital multimeter	AGILENT	34401A
3	Digital power meter	YOKOGAWA	WT230 / WT110
4	AC source	CHROMA	6590/6463/6520/6530
5	Electronic load	H&H	ZS1880/ZS7060/ZS4260
6	Electronic load	CHROMA	63202 / 63204
7	Leakage current tester	KIKUSUI	TOS3200
8	Voltage probe	YOKOGAWA	701939/701944
9	Current probe	YOKOGAWA	701933
10	Inrush Current Meter	TAKAMISAWA	PSA-210
11	Data acquisition / switch unit	AGILENT	34970A
12	Controlled temp. chamber	THERMOTRON	SM-16-3800
13	Controlled temp. chamber	THERMOTRON	SM-16-8200
14	Controlled temp. chamber	THERMOTRON	SE-600-5-5
15	Controlled temp. chamber	THERMOTRON	SE-600-6-6

2. CHARACTERISTIC

2.1 Steady state data

(1) Regulation - Line & Load, Temperature drift

Z160-1.3

Conditions: Ta = 25°C

1. Regulation - Line & Load, C.V mode (Readings in [V])

	Vin (AC)					
Io	**85**	**100**	**200**	**265**	**Line Regulation**	
0%	159.9978	159.9977	159.9975	159.9980	0.5	0.000
25%	159.9974	159.9975	159.9974	159.9977	0.3	0.000
50%	159.9973	159.9967	159.9970	159.9972	0.6	0.000
75%	159.9970	159.9969	159.9970	159.9971	0.2	0.000
100%	159.9968	159.9971	159.9967	159.9972	0.5	0.000
Load Regulation	1.0	1.0	0.8	0.9	**ΔV(mV)**	**(%)**
	0.001	0.001	0.001	0.001	**(%)**	

2. Temperature drift, C.V mode

Conditions: Vin:100Vac
Iout:100%

Ta	**0°C**	**25°C**	**50°C**	**Temp. Coefficient (0°C~50°C)**	
Vout	159.996	159.984	159.995	12 mV	3 ppm/°C

2.1 Steady state data

(1) Regulation - Line & Load, Temperature drift

Z650-0.32

Conditions: Ta = 25°C

1. Regulation - Line & Load, C.V mode (Readings in [V])

	Vin (AC)					
Io	**85**	**100**	**200**	**265**	**Line Regulation**	
0%	649.9770	649.9788	649.9795	649.9808	3.8	0.001
25%	649.9814	649.9820	649.9816	649.9826	1.2	0.000
50%	649.9820	649.9824	649.9821	649.9832	1.2	0.000
75%	649.9821	649.9833	649.9823	649.9837	1.6	0.000
100%	649.9813	649.9830	649.9810	649.9827	2.0	0.000
Load Regulation	5.1	4.5	2.8	2.9	**ΔV(mV)**	**(%)**
	0.001	0.001	0.000	0.000	**(%)**	

2. Temperature drift, C.V mode

Conditions: Vin:100Vac
Iout:100%

Ta	**0°C**	**25°C**	**50°C**	**Temp. Coefficient (0°C~50°C)**	
Vout	650.026	649.996	649.992	34 mV	1 ppm/°C

2.1 Steady state data

(1) Regulation - Line & Load, Temperature drift

Z160-1.3

Conditions: Ta = 25°C

1. Regulation - Line & Load, C.C mode (*) (Readings in [A])

	Vin (AC)					
Vo	**85**	**100**	**200**	**265**	**Line Regulation**	
0%	1.2995	1.2995	1.2995	1.2995	0.0	0.000
25%	1.2995	1.2995	1.2995	1.2995	0.0	0.000
50%	1.2995	1.2995	1.2995	1.2995	0.0	0.000
75%	1.2994	1.2994	1.2994	1.2994	0.0	0.000
100%	1.2994	1.2994	1.2994	1.2994	0.0	0.000
Load Regulation	0.1	0.1	0.1	0.1	**ΔI(mA)**	**(%)**
	0.008	0.008	0.008	0.008	**(%)**	

Notes:
(*) Not including load regulation thermal drift effect.

2. Temperature drift, C.C mode

Conditions: Vin:100Vac
Iout:100%

Ta	**0°C**	**25°C**	**50°C**	**Temp. Coefficient (0°C~50°C)**	
Iout	1.2995	1.3000	1.2990	1.0 mA	30 ppm/°C

2.1 Steady state data

(1) Regulation - Line & Load, Temperature drift

Z650-0.32

Conditions: Ta = 25°C

1. Regulation - Line & Load, C.C mode (*) (Readings in [A])

	Vin (AC)					
Vo	**85**	**100**	**200**	**265**	**Line Regulation**	
Short	0.3200	0.3200	0.3201	0.3201	0.01	0.003
25%	0.3200	0.3200	0.3200	0.3200	0.01	0.003
50%	0.3200	0.3200	0.3200	0.3200	0.01	0.003
75%	0.3199	0.3200	0.3200	0.3200	0.02	0.006
100%	0.3199	0.3199	0.3199	0.3199	0.01	0.003
Load Regulation	0.1	0.1	0.1	0.1	**ΔI(mA)**	**(%)**
	0.034	0.034	0.038	0.041	**(%)**	

Notes:
(*) Not including load regulation thermal drift effect.

2. Temperature drift, C.C mode

Conditions: Vin:100Vac
Iout:100%

Ta	**0°C**	**25°C**	**50°C**	**Temp. Coefficient (0°C~50°C)**	
Iout	0.3204	0.3204	0.3206	0.2 mA	10 ppm/°C

2.1 Steady state data

(2) Output voltage and ripple voltage v.s input voltage

C.V mode

Conditions: Iout:100%

Z160-1.3

Ta: 0°C ---------- 25°C -·-·-·-·- 50°C ————

(3) Output current and ripple current v.s input voltage

C.C mode

Conditions: Vout:100%

Z160-1.3

Ta: 0°C ---------- 25°C -·-·-·-·- 50°C ————

2.1 Steady state data

(2) Output voltage and ripple voltage v.s input voltage

C.V mode

Conditions: Iout:100%

Z650-0.32

Ta: 0°C ---------- 25°C -·-·-·-·- 50°C ————

(3) Output current and ripple current v.s input voltage

C.C mode

Conditions: Vout:100%

Z650-0.32

Ta: 0°C ---------- 25°C -·-·-·-·- 50°C ————

2.1 Steady state data

(4) Efficiency and Input current vs. Output current

Conditions:

Vin: 85 VAC
100VAC
200 VAC
265 VAC
Vout:100%
Ta: 25°C

Z160-1.3

2.1 Steady state data

(4) Efficiency and Input current vs. Output current

Conditions:

Vin: 85 VAC
100VAC
200 VAC
265 VAC
Vout:100%
Ta: 25°C

Z650-0.32

2.2 Warm up drift & stability

Conditions: Vin:100Vac
Vout: 100%
Iout: 100%
Ta = 25°C

C.V mode

Z160-1.3

C.C mode

Z160-1.3

2.2 Warm up drift & stability

Conditions: Vin:100Vac
Vout: 100%
Iout: 100%
Ta = 25°C

C.V mode

Z650-0.32

C.C mode

Z650-0.32

2.3 Over voltage protection (OVP) characteristics

Conditions: Vin:100Vac
Iout: 0%
Ta = 25°C

Z160-1.3

OVP setting: 176V

Z650-0.32

OVP setting: 717V

2.4 ON/OFF Output rise characteristics

Conditions: Vin:100Vac
Vout: 100%
Iout: 0%
Iset=105%
Ta = 25°C

C.V mode

Z160-1.3

50V/DIV	20ms/DIV

Z650-0.32

200V/DIV	20ms/DIV

2.4 ON/OFF Output rise characteristics

Conditions: Vin:100Vac
Vout: 100%
Iout: 100%
Iset=105%
Load: CR
Ta = 25°C

C.V mode

Z160-1.3

50V/DIV	50ms/DIV

Z650-0.32

200V/DIV	50ms/DIV

2.4 ON/OFF Output rise characteristics

Conditions: Vin:100Vac
Vout: 100%
Iout: 100%
Vset=105%
Load: CR
Ta = 25°C

C.C mode

Z160-1.3

0.5A/DIV	100ms/DIV

Z650-0.32

0.1A/DIV	100ms/DIV

2.4 ON/OFF Output rise characteristics

Conditions: Vin:100Vac
Iout: 100%
Vset=105%
shorted output
Ta = 25°C

C.C mode

Z160-1.3

0.5A/DIV	20ms/DIV

Z650-0.32

0.1A/DIV	20ms/DIV

2.5 ON/OFF Output fall characteristics

Conditions: Vin:100Vac
Vout: 100%
Iout: 0%
Iset=105%
Ta = 25°C

C.V mode

Z160-1.3

50V/DIV	500ms/DIV

Z650-0.32

200V/DIV	1s/DIV

2.5 ON/OFF Output fall characteristics

Conditions: Vin:100Vac
Vout: 100%
Iout: 100%
Iset=105%
Load: CR
Ta = 25°C

C.V mode

Z160-1.3

Z650-0.32

2.5 ON/OFF Output fall characteristics

Conditions: Vin:100Vac
Vout: 100%
Iout: 100%
Vset=105%
Load: CR
Ta = 25°C

C.C mode

Z160-1.3

0.5A/DIV	100ms/DIV

Z650-0.32

0.1A/DIV	100ms/DIV

2.5 ON/OFF Output fall characteristics

Conditions: Vin:100Vac
Iout: 100%
Vset=105%
shorted output
Ta = 25°C

C.C mode

Z160-1.3

$0.5^{A}/_{DIV}$	$0.5^{ms}/_{DIV}$

Z650-0.32

$0.1^{A}/_{DIV}$	$2^{ms}/_{DIV}$

2.6 Hold up time characteristics

Conditions: Vin:100Vac
Vout: 100%
Ta = 25°C

Z160-1.3

2.6 Hold up time characteristics

Conditions: Vin:100Vac
Vout: 100%
Ta = 25°C

Z650-0.32

2.7 Dynamic line response characteristics

Conditions: Vin:85↔132V
Vout: 100%
Iout: 100%
Ta = 25°C

C.V mode

Z160-1.3

Conditions: Vin:170↔265V
Vout: 100%
Iout: 100%
Ta = 25°C

2.7 Dynamic line response characteristics

Conditions: Vin:85↔132V
Vout: 100%
Iout: 100%
Ta = 25°C

C.V mode

Z650-0.32

Conditions: Vin:170↔265V
Vout: 100%
Iout: 100%
Ta = 25°C

2.7 Dynamic line response characteristics

Conditions: Vin:85↔132V
Vout: 100%
Iout: 100%
Ta = 25°C

C.C mode

Z160-1.3

Conditions: Vin:170↔265V
Vout: 100%
Iout: 100%
Ta = 25°C

2.7 Dynamic line response characteristics

Conditions: Vin:85↔132V
Vout: 100%
Iout: 100%
Ta = 25°C

C.C mode

Z650-0.32

Conditions: Vin:170↔265V
Vout: 100%
Iout: 100%
Ta = 25°C

2.8 Dynamic load response characteristics

Conditions: Vin:100Vac
Vout: 100%
Ta = 25°C

C.V mode

Load current: tr=tf=100us

Z160-1.3

Iout:0%↔100%	f:100HZ

0.2V/DIV	2ms/DIV
0.14%	-0.20%

Iout:50%↔100%	f:100HZ

0.1V/DIV	2ms/DIV
0.10%	-0.10%

Iout:0%↔100%	f:1000HZ

0.2V/DIV	200us/DIV
0.10%	-0.12%

Iout:50%↔100%	f:1000HZ

0.1V/DIV	200us/DIV
0.05%	-0.05%

2.8 Dynamic load response characteristics

Conditions: Vin:100Vac
Vout: 100%
Ta = 25°C

C.V mode

Z650-0.32

Iout:0%↔100%	f:100HZ

1V/DIV	2ms/DIV
0.13%	-0.20%

Iout:50%↔100%	f:100HZ

0.5V/DIV	2ms/DIV
0.05%	-0.04%

Iout:0%↔100%	f:1000HZ

0.5V/DIV	200us/DIV
0.03%	-0.03%

Iout:50%↔100%	f:1000HZ

0.2V/DIV	200us/DIV
0.02%	-0.02%

2.8 Dynamic load response characteristics

Conditions: Vin:100Vac
Ta = 25°C

C.C mode

Z160-1.3

Io=1.3A

Vout:144↔120V	f:10HZ

0.2A/DIV	20ms/DIV
19.70%	-17.30%

Io=0.65A

Vout:144↔120V	f:10HZ

0.1A/DIV	20ms/DIV
9.00%	-8.46%

Z650-0.32

Io=0.32A

Vout:585↔487.5V	f:10HZ

0.05A/DIV	20ms/DIV
19.79%	-17.50%

Io=0.16A

Vout:585↔487.5V	f:10HZ

0.02A/DIV	20ms/DIV
10.10%	-9.18%

2.9 Response to brown-out characteristics

Conditions: Vin:100VAC
Vout: 100%
Iout: 100%
Ta = 25°C

C.V mode

Z160-1.3

Brown-out time
A - 34mS
C - 53mS

2.9 Response to brown-out characteristics

Conditions: Vin:100VAC
Vout: 100%
Iout: 100%
Ta = 25°C

C.V mode

Z650-0.32

Brown-out time
A - 19ms
B - 44ms
C - 60ms

2.9 Response to brown-out characteristics

Conditions: Vin:100VAC
Vout: 100%
Iout: 100%
Ta = 25°C

C.C mode

Z160-1.3

Brown-out time
A - 32mS
B - 35mS
C -65mS

2.9 Response to brown-out characteristics

Conditions: Vin:100VAC
Vout: 100%
Iout: 100%
Ta = 25°C

C.C mode

Z650-0.32

Brown-out time
A - 19mS
B - 45mS
C - 227mS

2.10 Inrush Current Characteristics during line brown outs

Conditions: Vin: 100VAC
Vout: 100%
Iout: 0% ----------
Iout: 100% ————
Ta = 25°C

Z160-1.3

2.10 Inrush Current Characteristics during line brown outs

Conditions: Vin: 200VAC
Vout: 100%
Iout: 0% ----------
Iout: 100% ————
Ta = 25°C

Z650-0.32

2.11 Inrush current waveform

Conditions: Vin: 100V
Vout: 100%
Iout: 100%
Ta = 25°C

Z160-1.3

Switch on phase angle of input AC voltage

Φ=0°

Switch on phase angle of input AC voltage

Φ=90°

2.11 Inrush current waveform

Conditions: Vin: 200V
Vout: 100%
Iout: 100%
Ta = 25°C

Z160-1.3

Switch on phase angle of input AC voltage

Φ=0°

Switch on phase angle of input AC voltage

Φ=90°

2.11 Inrush current waveform

Conditions: Vin: 100V
Vout: 100%
Iout: 100%
Ta = 25°C

Z650-0.32

Switch on phase angle of input AC voltage

Φ=0°

Switch on phase angle of input AC voltage

Φ=90°

2.11 Inrush current waveform

Conditions: Vin: 200V
Vout: 100%
Iout: 100%
Ta = 25°C

Z650-0.32

Switch on phase angle of input AC voltage

Φ=0°

Switch on phase angle of input AC voltage

Φ=90°

2.12 Input current waveform

Conditions: Vin: 100VAC
Vout: 100%
Iout: 100%
Ta = 25°C

Z160-1.3

Conditions: Vin: 200VAC
Vout: 100%
Iout: 100%
Ta = 25°C

2.12 Input current waveform

Conditions: Vin: 100VAC
Vout: 100%
Iout: 100%
Ta = 25°C

Z650-0.32

Conditions: Vin: 200VAC
Vout: 100%
Iout: 100%
Ta = 25°C

2.13 Leakage current characteristics

Conditions: Vin: 100~265Vac
Iout: 0% - - - - -
Iout:100% ———
Ta = 25°C
f=50HZ

Z650-0.32

2.14 Output voltage ripple & noise waveform

Conditions: Vin: 100VAC
Vout: 100%
Iout: 100%
Ta = 25°C

C.V mode

Normal Mode

Z160-1.3

5mV/DIV	5us/DIV

Z650-0.32

50mV/DIV	5us/DIV